

Service Protocol L-Service (annual)

Customer:		Vehicle:		
		Reg.No:		
Lift model:		Prod.No:		
C=Check R=Replace L=Lubrication * If the lift has the equipment				
Comments OK <input type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Service points		Information	See instructions for resp. lift models	
Mecanics (Visual inspection of any cracks and / or damage)				
C		1.1 Mounting bracket	Any cracks / damage, Torques	IE-0105 / IE-0104
C		1.2 Support frame	Any cracks / damage, drainage holes	IE-0105
C		1.3 Liftarm	Any cracks / damage	IE-0105
C		1.4 Platform	Any cracks / damage	IE-0105
C		1.5 Bumper bar	Any cracks / damage, Torques	IE-0105 / IE-0104
C		1.6 Cylinders	Any cracks / damage, gaiters	IE-0105
C		1.7 Pivot bolt, bushing (all)	Wear and tear, Torques	IE-0105 / IE-0104
C		1.8 Slide system*	Any cracks / damage, Torques, and functional check	IE-0105 / IE-0104
L		1.9 Lubrication	All lubrication points	IE-0101
C		1.10 Sealings against bodywork*	Wear and tear, condition	IE-0106
Hydraulics (sequence) of an oil change (Visual inspection of oil leak on the entire hydraulic system)				
C		2.1 Main fuse	Cleanliness, contact surfaces	IE-0103
R		2.2 Hydraulic oil	Changes	IE-0102
C		2.3 Hydraulic hoses	Oil leak, wear and tear, free movement	IE-0104
C		2.4 The system's leakproofness	Hydr.connection.unit+tank, cyl. torques	IE-0104
C		2.5 Pressure Relief Valve	Valve should open when tilting against body, check pressure if not opening.	IE-0108
C		2.6 Velocity lifting, lowering, tilting	That the lifts speed is within the correct range	IE-0111
Electrical equipment (check all the points cable and interfaces)				
C		3.1 Main power cable, ground cable	Wear and tear, attachment, contact surface	IE-0103
C		3.2 Control units	All functions of all control units	IE-0103
C		3.3 Connection box for control units	Tightness, cleanliness	IE-0103
C		3.4 Circuit card	Function, connections, wear and tear	IE-0103
C		3.5 Alarm for open platform	That the lamp shine when platform is not closed	IE-0103
C		3.6 Battery voltage, vehicle and lift inactive	Difference between the battery and hydraulic unit (not more than 6% dfference)	IE-0103
C		3.7 Cabin switch*	Functional test	IE-0103
Signs, stickers (Visual inspection of the function and interpretable)				
C		4.1 Warning flags, -tape	2 pcs on platform, platform edge	IE-0107
C		4.2 Load chart	1 pc on platform, 1 pc outside control unit	IE-0107
C		4.3 Working area	Sticker on platform	IE-0107
C		4.4 Instruction control units	Outside control unit	IE-0107
C		4.5 Type plate	Is firmly attached and is INTERPRETABLE	IE-0107

Note: If comment is marked for any of the service points; complete the task below

Service control.

(Mark the box for actions performed for each. service point.)

Service-points	Comments / Actions

Inspection performed:

Actions performed:

Signature..... Signature.....

Date.....

Date.....

Company stamp

Company stamp