Service Protocol L-Service (annual)

Customer:	Vehicle:
	Reg.No:
Lift model:	Prod.No:

C=Check R=Replace L=Lubrication * If the lift has the equipment

Comments OK	Service points	Information	See instructions for resp. lift models
	Mecanics (Visual inspection of any cracks and / or damage)		**IE-0110**
C	1.1 Mounting bracket	Any cracks / damage, Torques	IE-0105 / IE-0104
C	1.2 Support frame	Any cracks / damage, drainage holes	IE-0105
C	1.3 Liftarm	Any cracks / damage	IE-0105
C	1.4 Platform	Any cracks / damage	IE-0105
C	1.5 Bumper bar	Any cracks / damage, Torques	IE-0105 / IE-0104
C	1.6 Cylinders	Any cracks / damage, gaiters	IE-0105
C	1.7 Pivot bolt, bushing (all)	Wear and tear, Torques	IE-0105 / IE-0104
C	1.8 Slide system*	Any cracks / damage, Torques, and functional check	IE-0105 / IE-0104
L	1.9 Lubrication	All lubrication points	IE-0101
C	1.10 Sealings against bodywork*	Wear and tear, condition	IE-0106
	Hydraulics (sequence) of an oil change (Visual inspection of oil leak on the entire hydraulic system)		**IE-0109**
C	2.1 Main fuse	Cleanliness, contact surfaces	IE-0103
R	2.2 Hydraulic oil	NB! Only at XL-Service IF equipped with oil filter	IE-0102
	2.3 Oil filter*	Changes at XL-Service. Every three years	
C	2.4 Hydraulic hoses	Oil leak, wear and tear, free movement	IE-0104
C	2.5 The system's leakproofness	Hydr.connection.unit+tank, cyl. torques	IE-0104
C	2.6 Pressure Relief Valve	Valve should open when tilting against body, check pressure if not opening.	IE-0108
C	2.7 Velocity lifting, lowering, tilting	That the lifts speed is within the correct range	IE-0111
	Electrical equipment (check all the points cable and interfaces)		
C	3.1 Main power cable, ground cable	Wear and tear, attachment, contact surface	IE-0103
C	3.2 Control units	All functions of all control units	IE-0103
C	3.3 Connection box for control units	Tightness, cleanliness	IE-0103
C	3.4 Circuit card	Function, connections, wear and tear	IE-0103
C	3.5 Alarm for open platform	That the lamp shine when platform is not closed	IE-0103
C	3.6 Battery voltage, vehicle and lift inactive	Difference between the battery and hydraulic unit (not more than 6% dfference)	IE-0103
C	3.7 Cabin switch*	Functional test	IE-0103
	Signs, stickers (Visual inspection of the function and interpretable)		
C	4.1 Warning flags, -tape	2 pcs on platform, platfrom edge	IE-0107
C	4.2 Load chart	1 pc on platform, 1 pc outside control unit	IE-0107
C	4.3 Working area	Sticker on platform	IE-0107
C	4.4 Instruction control units	Outside control unit	IE-0107
C	4.5 Type plate	Is firmly attached and is INTERPRETABLE	IE-0107

Note: If comment is marked for any of the service points; complete the task below

Service control.
(Mark the box for actions performed for each. service point.)

Service-points	Comments / Actions

Inspection performed:

Signature.....

Date.....

Company stamp

Actions performed:

Signature.....

Date.....

Company stamp